

▶▶ STC-1530DN



- Vandal/Water Resistant Tank Camera...
- Optional High Impact Toughened Glass Lens...
- Precision Spun Aluminium Housing Body...
- Stainless Steel "U" Shaped Mounting Bracket...
- True Day/Night with removable IR-Cut Filter...
- Compact 70mm(Ø) x 100mm(L) Housing...
- Ingress Protection Rating = IP-67 Housing...
- Special Cable Entry Gland = IP-68 Rating...
- Camera Module 530TV Lines, 0.01Lux...
- Camera Module Engineered in JAPAN...
- Camera Housing Made in AUSTRALIA...
- Specified for Marine Application...
- Specified for External use...
- Optional 3.7~12mm Vari-Focal DC Iris Lens...

3 Years Warranty

SPECIFICATIONS

Vandal & Water Resistant Tank Camera, Aluminium Body with D-Mount Lens...
[External Use] IP-67...

| | |
|---------------------------|---|
| Image Sensor | 1/3" interline Type CCD (SONY EX-View HAD CCD) |
| Effective Picture Element | 752 (H) x 582 (V) |
| Scanning System | 2 : 1 Interlace |
| Synchronisation System | Internal |
| Horizontal Resolution | 530 TV-Lines (High Resolution) |
| Minimum Illumination | 0.01 lux (Video Output 50% AGC On (F1.4)) |
| Gain Control | ON / OFF (Max 0dB ~24dB) |
| Signal to Noise Ratio | 50dB or better |
| Gamma Characteristics | $\gamma = 0.45$ |
| Back Light Compensation | ON / OFF |
| Electronic Iris | 1/50 ~ 1/30,000 sec. |
| Auto Iris | Video & DC Drive Circuit |
| Shutter Speed | (Variable) |
| White Balance | ATW (2600°K ~ 9000°K) |
| Remote Control Software | N/A |
| Digital Zoom | N/A |
| Mirror Image (Flip) | N/A |
| OSD setting | N/A |
| Camera Title (ID) | N/A |
| Voltage Supply | Regulated 12vDC (+/-) 10% |
| Power Consumption | 200mA @ 12vDC |
| Dimensions / Weight | 70mm(Ø) x 100mm(L) - Approx. 600g |
| Operating Temp. / Humid. | (-)5°C ~ (+)40°C / 20% ~ 80% Keep free from damp |
| Storage Temp. / Humid. | (-)20°C ~ (+)60°C / 20% ~ 80% & humid conditions. |

LENS OPTIONS

"Button" 1/3" D-Mount Lens options

| | |
|--------------------|--|
| CL-23/2 | f=2.3mm - F2.0 Mini Lens (114°) Horizontal Viewing Angle... |
| CL-40/2 (standard) | f=4.0mm - F2.0 Mini Lens (68°) Horizontal Viewing Angle... |
| CL-56/3 | f=5.6mm - F3.0 Mini Lens (47°) Horizontal Viewing Angle... |
| CL-80/4 | f=8.0mm - F4.0 Mini Lens (32°) Horizontal Viewing Angle... |
| CL-160/2 | f=16.0mm - F2.0 Mini Lens (20°) Horizontal Viewing Angle... |
| CL-3712/16 | f=3.7~12.0mm - F1.6 VF-DC Lens (75°~27°) Horizontal Angle... |